



COOPERTIRES



CS2

The Cooper **CS2** offers good value performance in a popular range of sizes. With European roads in mind, the unique tread pattern design offers low road noise, durability and value for money.





CS2

SD						
60 Series						
165/60R14	75T	5.0	4.5 - 6.0	170	554	
185/60R14	82T	5.5	5.0 - 6.5	189	578	
65 Series						
155/65R13	73T	4.5	4.5 - 5.5	157	532	
165/65R13	77T	5.0	4.5 - 6.0	170	544	
175/65R13	80T	5.0	5.0 - 6.0	177	558	
155/65R14	75T	5.0	4.5 - 6.0	170	570	
165/65R14	79T	5.0	4.5 - 6.0	170	570	
175/65R14	82T	5.0	5.0 - 6.0	177	584	
175/65R14 XL	86T	5.0	5.0 - 6.0	177	584	
185/65R14	86T	5.5	5.0 - 6.5	189	596	
165/65R15	81T	5.0	4.5 - 6.0	170	595	
175/65R15	84T	5.0	5.0 - 6.0	177	609	
185/65R15	88T	5.5	5.0 - 6.5	189	621	
195/65R15	91T	6.0	5.5 - 7.0	201	635	
195/65R15	95T	6.0	5.5 - 7.0	201	635	
70 Series						
155/70R13	79T	5.0	4.0 - 5.5	170	562	
165/70R13	79T	5.0	4.0 - 5.5	170	562	
175/70R13	82T	5.0	4.5 - 6.0	177	576	
165/70R14	81T	5.0	4.0 - 5.5	170	588	
165/70R14 XL	85T	5.0	4.0 - 5.5	170	588	
175/70R14	84T	5.0	4.5 - 6.0	177	602	
175/70R14 XL	88T	5.0	4.5 - 6.0	177	602	
185/70R14	88T	5.5	4.5 - 6.0	189	616	

CS2

Rolling Resistance: Better fuel economy than its equivalent predecessor due to an average 7% lower rolling resistance.

Tread Wear: Longer tyre life due to a new tread compound, a new tread design and structural enhancements (resulting in a 10% improvement over its predecessor).

Tread pattern: Asymmetric tread design with computer-designed pitch sequence for a quieter ride. Broad solid outer shoulder for enhanced handling performance.

Environmentally friendly: using zero polycyclic aromatic hydrocarbons (PAH) conforming to EU directive 2005/69.

Legislation: Conforms to all the applicable EU legislation for noise and wet grip.

T-Speed Rated: In popular European sizes to fit a range of small family cars.

RATING	KM/H	MPH	RATING	KM/H	MPH	RATING	KM/H	MPH
N	140	87	S	180	112	V	240	149
Q	160	99	T	190	118	W	270	168
R	170	106	H	210	130	Y	300	186

SYMBOLS KEY

- SD SERVICE DESCRIPTION
- RECOMMENDED RIM WIDTH
- APPROVED RIM WIDTH - MIN/MAX
- SECTION WIDTH
- OVERALL DIAMETER

1 Tread Design: The three wide circumferential grooves, with the open inner shoulders help provide excellent aquaplaning resistance.



For speed symbols V,W & Y load capacity reductions of up to 15% apply, above 210 Km/h for V-rated tyres, 240 Km/h for W-rated tyres & 270 Km/h for Y-rated tyres. Please consult Cooper Tire & Rubber Company for further information.

