

The new generation of 4x4 tyres for maximum fun, comfort and safety is ready.



Pattern

- 1 Nodges for additional grip on loose terrains
- 2 Micro sipe block structure as a draining system ensures further wet performance
- 3 Shifted and angled blocks for excellent traction and handling performance off road
- 4 Traction ridges provide additional grip on mud and green
- 5 Continuing main grooves for unhindered water flow and self-cleaning
- 6 Open shoulder for better self-cleaning effect

Vehicle Examples

| | |
|-----------|------------|
| BMW | MITSUBISHI |
| JEEP | NISSAN |
| LANDROVER | TOYOTA |
| MERCEDES | VW |



GRABBER™ AT



Product Features

| Feature | Effect | Benefit |
|---|---|---|
| ▷ Shifted shoulder and angled center blocks with nodges | ▷ Excellent transmission of high lateral and circumferential forces | ▷ Outstanding traction ▷ Excellent steering performance off road |
| ▷ Open shoulders in line with central traction grooves | ▷ Self-cleaning effect from centre to shoulder | ▷ High grip in muddy terrain |
| ▷ Solid, stiffness and flexibility balanced blocks | ▷ Flexibility against cut and chip, stiffness against aggressive forces | ▷ Robust tread pattern even in rough terrain |
| ▷ V-shaped grooves and turning block edges | ▷ Stone retention avoids tyre damages | ▷ Long lasting in rough conditions |
| ▷ Angled block and sipe orientation | ▷ Smooth rolling in and out of block edges | ▷ High comfort and low riding noise |
| ▷ Continuing main grooves and siped blocks | ▷ Draining of tread pattern | ▷ Best aquaplaning and wet performance on flooded roads and tracks |



The General Tire 4x4 tyre – Grabber AT – is designed specifically to offer high grip and good handling in both on- and off-road applications. The rugged structure of the Grabber AT protects the tread and sidewall from damage, whilst ensuring comfortable driving characteristics and high mileage performance. The new tyre compound and tread pattern has been developed with the emphasis on safety for on road and off road. The wet braking and noise reduction performance is better than its predecessor. Therefore this AT tyre (All Terrain) is the solution of General Tire for increased demands for on road driving.

General Tire Grabber™ AT

Dimensions

| PATTERN | RIM DIA-METER | SIZE | SPEED/LOAD INDEX | LOAD RANGE | SIDE-WALL | RIM PROTEC-TION | PERMITTED RIMS WIDTH | | TYRE DIMENSIONS | | TREAD PATTERN DEPTH (MM) | ROLLING CIRCUM-FERENCE (+1,5% / -2,5% MM) | |
|--------------------------|--------------------|--------------------|------------------|------------|-----------|-----------------|----------------------|------|------------------------------|-----------------------------|--------------------------|---|------|
| | | | | | | | MIN. (INCH) | MAX. | MAX. IN SERVICE OUTER-Ø (MM) | ON MEASURING RIM WIDTH (MM) | | | |
| AT | 14" | 27x8.50 R 14 LT * | 95 Q | C | OWL | FR | 6.0 | 7.5 | 693 | 235 | 13.1 | 2076 | |
| | 15" | 205/75 R 15 | 97 T | | BSW | FR | 5.5 | 7.0 | 701 | 211 | 11.2 | 2100 | |
| | | 215/75 R 15 | 100 S | | BSW | FR | 5.5 | 7.0 | 715 | 225 | 11.2 | 2142 | |
| | | 225/75 R 15 | 102 S | | BSW | FR | 6.0 | 7.5 | 733 | 232 | 11.2 | 2195 | |
| | | LT235/75 R 15 * | 104/101 Q | E | OWL | FR | 6.0 | 7.0 | 753 | 249 | 13.1 | 2255 | |
| | | 235/75 R 15 * | 105 S | | OWL | FR | 6.0 | 8.0 | 747 | 244 | 11.2 | 2237 | |
| | | 225/70 R 15 | 100 S | | BSW | FR | 6.0 | 7.5 | 709 | 237 | 11.2 | 2124 | |
| | | 255/70 R 15 | 108 S | | BSW | FR | 6.5 | 8.5 | 753 | 270 | 11.2 | 2255 | |
| | | 265/70 R 15 | 112 S | | BSW | FR | 7.0 | 9.0 | 767 | 282 | 11.2 | 2296 | |
| | | LT30x9.50 R 15 | 104 S | C | OWL | FR | 6.5 | 8.5 | 771 | 260 | 13.1 | 2308 | |
| | | 31x10.50 R 15 LT | 109 Q | C | OWL | FR | 7.0 | 9.0 | 797 | 289 | 13.1 | 2386 | |
| | | 33x10.50 R 15 LT * | 114 Q | C | BSW | FR | 6.5 | 8.5 | 844 | 289 | 8.7 | 2525 | |
| | | 35x12.50 R 15 LT * | 113 Q | C | BSW | FR | 8.5 | 11.0 | 897 | 343 | 13.1 | 2682 | |
| | | 16" | LT235/85 R 16 | 120/116 Q | E | OWL | FR | 6.0 | 7.5 | 828 | 249 | 13.1 | 2478 |
| | | | LT245/75 R 16 | 120/116 Q | E | OWL | FR | 6.5 | 8.0 | 795 | 263 | 13.1 | 2380 |
| | | | LT265/75 R 16 * | 123/120 Q | E | OWL | FR | 7.0 | 8.0 | 826 | 283 | 13.1 | 2472 |
| | LT285/75 R 16 | | 126/123 Q | E | OWL | FR | 7.5 | 9.0 | 858 | 303 | 13.1 | 2567 | |
| | LT315/75 R 16 * | | 127/124 Q | E | OWL | FR | 8.0 | 11.0 | 904 | 332 | 13.1 | 2703 | |
| | 215/70 R 16 | | 100 T | | BSW | FR | 5.0 | 7.0 | 720 | 230 | 11.2 | 2157 | |
| | 235/70 R 16 | | 106 S | | OWL | FR | 6.0 | 8.0 | 750 | 250 | 11.2 | 2247 | |
| | 245/70 R 16 | | 107 S | | OWL | FR | 6.5 | 8.0 | 764 | 258 | 11.2 | 2288 | |
| | 255/70 R 16 | | 111 S | | OWL | FR | 6.5 | 8.5 | 778 | 270 | 11.2 | 2330 | |
| | 265/70 R 16 * | | 112 S | | OWL | FR | 7.0 | 9.0 | 792 | 283 | 11.2 | 2371 | |
| | 265/70 R 16 | | 112 T | | BSW | FR | 7.0 | 9.0 | 792 | 283 | 11.2 | 2371 | |
| | LT305/70 R 16 * | | 124/121 Q | E | OWL | FR | 8.0 | 9.5 | 858 | 330 | 13.1 | 2567 | |
| | 215/65 R 16 | | 98 T | | BSW | FR | 6.0 | 7.5 | 698 | 230 | 11.2 | 2092 | |
| | 255/65 R 16 | | 109 T | | BSW | FR | 7.0 | 9.0 | 752 | 270 | 11.2 | 2252 | |
| | 17" | | LT235/80 R 17 * | 120/117 Q | E | OWL | FR | 6.0 | 7.5 | 830 | 249 | 13.1 | 2485 |
| | | | LT245/75 R 17 * | 121/118 Q | E | OWL | FR | 6.0 | 7.5 | 820 | 263 | 13.1 | 2455 |
| | | | LT245/70 R 17 | 119/116 Q | E | BSW | FR | 6.5 | 8.0 | 796 | 263 | 13.1 | 2384 |
| | | | LT265/70 R 17 * | 121/118 Q | E | OWL | FR | 7.0 | 8.5 | 826 | 288 | 13.1 | 2473 |
| | | LT285/70 R 17 * | 121/118 Q | D | OWL | FR | 7.5 | 9.0 | 854 | 310 | 13.1 | 2556 | |
| | | LT315/70 R 17 * | 121/118 Q | D | OWL | FR | 8.0 | 11.0 | 898 | 342 | 13.1 | 2686 | |
| | | 245/70 R 17 | 110 S | | BSW | FR | 6.5 | 8.0 | 790 | 258 | 11.2 | 2366 | |
| | | 255/70 R 17 * | 112 S | | OWL | FR | 6.5 | 8.5 | 804 | 270 | 11.2 | 2408 | |
| | | 265/70 R 17 | 115 S | | BSW | FR | 7.5 | 9.5 | 818 | 283 | 11.2 | 2449 | |
| | | 265/70 R 17 * | 115 S | | OWL | FR | 7.5 | 9.5 | 818 | 283 | 11.2 | 2449 | |
| | | 235/65 R 17 * | 104 S | | OWL | FR | 6.5 | 8.5 | 750 | 240 | 11.2 | 2247 | |
| | | 235/65 R 17 | 108 H | XL | BSW | FR | 6.5 | 8.5 | 750 | 240 | 10.8 | 2247 | |
| | | 255/65 R 17 * | 110 S | | OWL | FR | 7.0 | 9.0 | 778 | 270 | 11.2 | 2330 | |
| | | 255/65 R 17 | 110 H | | BSW | FR | 7.0 | 9.0 | 778 | 270 | 13.1 | 2330 | |
| | | 265/65 R 17 * | 112 S | | OWL | FR | 7.5 | 9.5 | 790 | 283 | 11.2 | 2366 | |
| | | 265/65 R 17 | 112 T | | BSW | FR | 7.5 | 9.5 | 790 | 283 | 11.2 | 2366 | |
| | | 33x12.50 R 17 LT * | 105 Q | C | OWL | FR | 8.5 | 11.0 | 848 | 343 | 13.1 | 2538 | |
| | | 18" | LT275/70 R 18 | 125/122 Q | E | OWL | FR | 7.0 | 8.5 | 865 | 296 | 13.1 | 2589 |
| | LT265/65 R 18 * | | 122/119 Q | E | OWL | FR | 7.0 | 9.5 | 821 | 288 | 13.1 | 2459 | |
| | LT275/65 R 18 * | | 123/120 Q | E | OWL | FR | 7.5 | 9.0 | 835 | 296 | 13.1 | 2500 | |
| 265/70 R 18 * | 116 S | | | OWL | FR | 7.0 | 9.0 | 843 | 283 | 11.2 | 2524 | | |
| 255/60 R 18 | 112 H | | XL | BSW | FR | 7.0 | 9.0 | 755 | 270 | 10.8 | 2263 | | |
| 265/60 R 18 * | 110 T | | | OWL | FR | 7.5 | 9.5 | 787 | 283 | 11.2 | 2358 | | |
| 255/55 R 18 | 109 H | | XL | BWS | FR | 7.0 | 9.0 | 749 | 276 | 10.8 | 2245 | | |
| 33x12.50 R 18 LT * | 118 Q | | E | OWL | FR | 8.5 | 11.0 | 847 | 343 | 13.1 | 2536 | | |
| 35x12.50 R 18 LT * | 123 Q | | E | OWL | FR | 8.5 | 11.0 | 900 | 343 | 13.1 | 2693 | | |
| 19" | 255/55 R 19 | | 111 H | XL | BSW | FR | 7.0 | 9.0 | 775 | 276 | 10.8 | 2323 | |
| | 255/50 R 19 | | 107 H | XL | BSW | FR | 7.0 | 9.0 | 749 | 276 | 10.8 | 2245 | |
| 20" | LT275/65 R 20 * | | 126/123 Q | E | OWL | FR | 7.0 | 9.5 | 886 | 296 | 13.1 | 2653 | |
| | 275/60 R 20 * | 115 S | | BSW | FR | 7.5 | 9.5 | 852 | 290 | 11.2 | 2552 | | |
| | LT305/55 R 20 * | 121/118 Q | E | BSW | FR | 8.5 | 11.0 | 864 | 335 | 13.1 | 2588 | | |
| | LT315/50 R 20 * | 112/109 Q | D | BSW | FR | 8.5 | 11.0 | 842 | 348 | 13.1 | 2522 | | |
| | 305/50 R 20 * | 120 T | XL | BSW | FR | 8.5 | 11.0 | 826 | 329 | 11.2 | 2475 | | |
| | 275/45 R 20 | 110 H | XL | BSW | FR | 8.5 | 10.5 | 766 | 284 | 10.8 | 2297 | | |
| | 275/40 R 20 | 106 H | XL | BSW | FR | 9.0 | 11.0 | 670 | 302 | 10.8 | 2011 | | |
| | 35x12.50 R 20 LT * | 121 Q | E | OWL | FR | 8.5 | 11.0 | 898 | 343 | 13.1 | 2689 | | |
| * Size available in 2012 | | | | | | | | | | | | | |
| AT2 | 15" | 235/75 R 15 | 109 S | XL | OWL | FR | 6.0 | 8.0 | 747 | 244 | 11.2 | 2237 | |
| | 16" | 225/75 R 16 | 108 S | XL | OWL | FR | 6.0 | 7.5 | 758 | 232 | 11.2 | 2269 | |
| | | LT235/85 R 16 | 120/116 S | E | OWL | FR | 6.0 | 7.5 | 828 | 249 | 13.1 | 2478 | |
| | | LT265/75 R 16 | 123/120 Q | E | OWL | FR | 7.0 | 8.0 | 826 | 283 | 13.1 | 2472 | |

Get into the World of General Tire

An off road feeling in a new dimension

Grabber New Generation

GRABBER™ AT

