

PROXES C1S

The Proxes C1S is designed for premium and luxury sedans. The Proxes C1S provides high grip levels and sharp steering response while also providing a comfortable and quiet ride.



FEATURES	BENEFITS
"Silent Wall" circumferential grooves.	Minimized tread noise (high pitch) on smooth road surfaces.
Asymmetric tread design with wide rib at shoulder with twin narrow grooves.	Good high speed stability and dry cornering grip.
Wide rib at quarter point and narrow groove with dimple.	Good dry and wet handling, directional stability and ride comfort.
Four wide circumferential grooves.	Water drainage suitable for heavy rain conditions.
Silica re-inforced tread compound.	High levels of wet & dry grip with low rolling resistance
Rim protector	Protects rim flanges from curb damage.
Wide edge-ply.	Re-inforced shoulder section to reduce of high- pitch road noise and optimize cornering performance.

DIMENSIONAL DATA - 15" & 16" Sizes

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES (INCH)
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			
195/65R15 91V	8.0	635	197	290	215	308	6.0	517	5.5 - 7.0
205/60R16 92W	8.1	652	206	299	225	316	6.0	504	5.5 7.5
215/60R16 95W	8.2	663	220	303	240	322	6.5	494	6.0 - 7.5
205/55R16 94W	7.6	632	210	291	229	307	6.5	518	5.5 - 7.5

PROXES C1S

DIMENSIONAL DATA - 17", 18" & 19" Sizes

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES (INCH)
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			
235/55R17 103W	7.9	691	242	317	264	335	7.5	475	6.5 - 8.5
215/55R17 98W	7.8	672	223	310	243	326	7.0	488	6.0 - 7.5
215/50R17 95W	7.7	649	220	301	240	315	7.0	505	6.0 - 7.5
225/50R17 98W	7.8	661	229	305	250	321	7.0	496	6.0 - 8.0
215/45R17 91W	7.9	630	210	293	229	306	7.0	520	7.0 - 8.0
225/45R17 94W	7.9	636	220	296	240	309	7.5	515	7.0 - 8.5
235/45R17 97W	8.1	647	237	300	258	314	8.0	507	7.5 - 9.0
215/45R18 93W	7.8	655	211	306	230	318	7.0	500	7.0 - 8.0
225/40R18 92W	8.0	641	228	300	249	311	8.0	512	7.5 - 9.0
245/45R18 100W	8.1	677	240	314	262	329	8.0	484	7.5 - 9.0
245/40R18 97W	8.1	655	244	306	266	318	8.5	500	8.0 - 9.5
255/45R18 103W	8.1	685	254	317	277	333	8.5	478	8.0 - 9.5
245/40R19 98W	8.1	682	245	319	267	331	8.0	481	8.0 - 9.5